

MECATOME T 400 SO

Specifications

- Automatic cut-off machine.
- Cut-off wheel Ø 400 mm
- Distance wheel/table 190 mm
- Cast iron table 400x400 mm
6 linear T-slots, 5 transversal T-slots.
- Variable wheel rotation speed 1500 to 3000 rpm
- Control panel with industrial knobs.
- Pump and 160 L tank
- Spray nozzle for cleaning
- Powerful light
- High accessibility to the large cutting chamber for easy loading of work piece.
- 400 V 3 phases 50 Hz
- Power 5,5 Kw
- Compliant with EEC standards.



Width (without control panel): 800 mm
Depth: 1300 mm
Height: 1800 mm
Weight: 650 kg.

Operating

- The MECATOME T 400 SO is an automatic high capacity cut-off machine. The downward movement with the automatic hydro-pneumatic pulse cutting system or direct cutting, is controlled by a flow regulator for fast and regular cuts.
 - The spray system and its pump are housed inside the cabinet.
 - Water cooling evacuation is located on the front part of cutting chamber for easy cleaning (hole Ø 70 mm)
 - Vertical movement 240 mm.
- Direct cut
Pulse cutting system.

With automatic operation and fast return stroke, the MECATOME T 400 SO lets the operator handle other tasks.

Accessories




- Quick clamping vices
- KOPAL holder
- Pump and tank with paper filtering 160 to 300 L.

Options

- Laser: red line on the workpiece, to locate the cut.
- Linear table: 400 x 400 mm, movement 200 mm
- Transversal table: 200 x 400 mm, movement 120 mm.

Cutting capacity

Distance wheel/table: 190 mm.

| Table | fixed | linear |
|---|------------------------------|--------|
|  | 154 mm | 145 mm |
|  | 145 x 160 mm | |
|  | 90 x 275 mm 1450 x 360 mm | |

TECNIMETAL

IGNACIO ELLACURÍA, 10-12
TELS. 91 356 22 94 - FAX: 91 355 58 08
28017 MADRID

38320 Brié et Angonnes - Grenoble
E-mail : presi@presi.com

E-mail: info@tecnimetalsa.com